



# ARMWOODSTRP WOOD STRIPPER

## PRODUCT DESCRIPTION

Specially formulated to remove oil-based finishes from all wood surfaces such as cedar, redwood, pine, cypress, fir and pressure-treated wood. It is ideal for use on wood decks, siding, fences, railings, steps and outdoor furniture.

### SPECS

SHELF LIFE	12 MONTHS
MIX RATIO	1 PART
WEIGHTPOT LIFE	8.70LBS
SOLIDS BY VOLUME	4.5
PACKAGING	1 GAL KIT
COLORS	CLEAR GREEN LIQUID
FREEZING POINT	12°F (-10°C).

### COVERAGE

One gallon of Wood Stripper will strip approximately 150-200 square feet of weathered oil finish. These rates may vary.

### COMPOSITION

Contains sodium hydroxide

### PACKAGING

Sold in 1 Gal Units

## RESTRICTIONS

Never mix or use with other chemicals, detergents, cleaners or with Problem-Solver Wood Brightener. Keep containers closed when not in use. Keep away from children. Protect screens, siding, windows and any metal flashing that are not intended to be stripped. Do not apply to hot or wet surfaces. Do not dilute with water.

This product is biodegradable. Protect any nearby plants, shrubs or other vegetation by wetting them down with water and covering them with plastic before application. Hose off shrubs and grass when job is complete.

Cleanup and Disposal: Rinse out container and application equipment thoroughly with water. Do not reuse container. Dispose of in accordance with local, state and federal regulations. Material Safety Data Sheet (MSDS) available upon request.

### SURFACE PREPARATION AND APPLICATION

Because it is difficult to determine the condition of the oil-based coating to be stripped, test the undiluted stripper on a small area to determine its effectiveness. Use Wood stripper to remove latex paints, stains and finishes. Wood Stripper is an oil-based paint, stain and varnish remover. It will remove paint or stain on adjacent surfaces not intended to be stripped. Apply liberally and evenly on a dry, cool surface using a brush, roller or pump-type sprayer. Let stand for a minimum of 15 minutes. Do not allow the stripper to dry. If it begins to dry, lightly mist with a garden hose. Rinse thoroughly with a garden hose with the nozzle at maximum pressure or use a pressure-washing unit. Do not exceed 1000 psi (pounds per square inch).

### IMPORTANT

All surfaces must be thoroughly neutralized with Wood Brightener rinsed and dried a minimum of 2 days prior to recoating, depending on the temperature and humidity. Any stripper not rinsed and neutralized from the surface will cause coating adhesion problems. Caution: Red cedar, redwood and mahogany will darken after the use of the stripper. The use of Wood Brightener immediately or within one day after stripping will brighten the wood back to its original color.

### PRECAUTIONS

When applying and rinsing Wood Stripper, walking surfaces, ladders and scaffolding may become slippery. Rinse all such surfaces thoroughly to remove overspray. Use wrap-around goggles with side shields, rubber gloves and protective footwear for protection from harmful chemicals. Remove any contaminated clothing immediately. Store at temperatures between 50°F (10°C) and 85°F (30°C). Keep from freezing. Use only when temperatures are between 50°F (10°C) and 90°F (32°C).

### MAINTENANCE

Wood Stripper must be neutralized with Wood Brightener.