

SAFETY DATA SHEETS
ArmorUltra Military Grade Topcoat Colored 352X- Part A



Page 1 – 2/23/2023

1. Product and Company Identification

Product Code: ARM352X-A
Product Name: ArmorUltra Military Grade Topcoat Colored 352X- Part A
Trade Name: ArmorUltra Military Grade Topcoat Colored 352X- Part A
Company Name: Armorpox Inc.
1260 North Ave
Plainfield, NJ 07062
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
CHEMTREC (800)424-9300

Emergency Contact:

Phone Number:
888-755-7361

2. Hazards Identification

Skin Corrosion/Irritation, Category 3
Flammable Liquids, Category 3
Toxic To Reproduction, Category 1B
Aquatic Toxicity (Acute), Category 3
Acute Toxicity: Skin, Category 4
Acute Toxicity: Inhalation, Category 4



GHS Signal Word:
GHS Hazard Phrases:

Danger

H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H332 - Harmful if inhaled.
H360 - May damage fertility or the unborn child.
H402 - Harmful to aquatic life.

GHS Precaution Phrases:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
P242 - Use only non-sparking tools.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P281 - Use personal protective equipment as required.

GHS Response Phrases:

P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 – Get medical attention/advice if you feel unwell.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this material.
Chronic inhalation may cause effects similar to those of acute inhalation.

GHS Storage and Disposal Phrases:

Potential Health Effects (Acute and Chronic):

Inhalation:

May be harmful if inhaled. Inhalation of vapor may cause respiratory tract irritation. Vapors may cause dizziness or suffocation. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma.

ArmorUltra Military Grade Topcoat Colored 352X- Part A/PAGE 2

Skin Contact:	May be harmful if absorbed through the skin. Causes skin irritation. Prolonged and/or repeated contact may cause irritation and/or dermatitis. Causes redness and pain.
Eye Contact:	Causes severe eye irritation. Causes redness and pain through the skin. Causes skin irritation.
Ingestion:	May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
Proprietary	Polyester poly-urethane	25.0 – 35.0%
13463-67-7	Titanium dioxide	35.0 – 45.0%
108-65-6	Propylene glycol methyl ether acetate	10.0 – 20.0%
1330-20-7	Xylene (mixed isomers)	1.0 – 5.0%
100-41-4	Ethylbenzene	0.1 – 1.0%

4. First Aid Measures

Emergency and First Aid Procedures:	
In Case of Inhalation:	If breathed in, move person into fresh air. Consult a physician. Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Get medical aid.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation or rash occurs, seek medical advice/attention.
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. Do NOT induce vomiting. Get medical aid immediately.
Signs and Symptoms Of Exposure:	Central nervous system depression. Dermatitis. Abdominal pain, Nausea, Vomiting, Anorexia. Shortness of breath.
Note to Physician:	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
Fire Fighting Instructions:	Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in the air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Personal precautions. Use personal protective equipment. Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.
---	---

ArmorUltra Military Grade Topcoat Colored 352X- Part A/PAGE 3

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge.

Precautions to be Taken in Storing:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

<u>CAS #</u>	<u>Partial Chemical Name</u>	<u>OSHA TWA</u>	<u>ACGIH TWA</u>
13463-67-7	Titanium Dioxide	PEL: 15 (dust) mg/m ³	TLV: 10 mg/m ³
Proprietary	Polyester Polyurethane	N/E	N/E
108-65-6	Propylene glycol methyl ether acetate	N/E	N/E
1330-20-7	Xylene (mixed isomers)	PEL: 100 PPM	TLV: 100 PPM
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 PPM STEL: 125 PPM

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation, etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	[] Gas	[X] Liquid	[X] Solid
Flash Point:	80°F		
Boiling Point:	220°F		
Explosive Limits:	LEL: 1.0	UEL: 7.1	
Weight Per Gallon:	12.5 +/-1		
Vapor Pressure (mm Hg):	7.1 @ 68°F		
Vapor Density:	Heavier than Air		
Evaporation Rate:	Slower than Ether		
Percent Volatile:	46 (Vol)		

10. Stability and Reactivity

Stability:	Unstable []	Stable [X]
Conditions to Avoid – Instability:	Heat, Flames and Sparks	
Incompatibility – Materials to Avoid:	Strong oxidizing agents	
Hazardous Decomposition Or Byproducts:	Nature of decomposition products unknown.	
Possibility of Hazardous Reactions: Conditions to Avoid – Hazardous Reactions:	Will occur []	Will not occur [X]
	No data available	

ArmorUltra Military Grade Topcoat Colored 352X- Part A/PAGE 4

11. Toxicological Information

Toxicological Information:

Epidemiology: No data available.
Teratogenicity: No data available.
Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: Acute toxicity.

Irritation or Corrosion:

Skin - Human - Mild skin irritation - -3 d.

Serious eye damage/eye irritation:


Sensitization:

No data available.

Carcinogenicity/Other Information:

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

 This product contains the following substances known to the State of California to cause cancer, birth defects or other reproductive hazards: Benzene, Toluene.

12. Ecological Information

General Ecological Information:

No data available

Persistence and Degradability:

No data available

Bioaccumulative Potential:

No data available

Mobility in Soil:

No data available

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

Limited Quantity – Used for 1 gallon containers when shipped in the United States of America

DOT Proper Shipping Name:

UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



Marine Transport IMDG Shipping: UN 1263, Paint Related Material, 3 PG III



AIR TRANSPORT (ICAO/IATA):

IATA Shipping Name:

UN 1263, Paint Related Material, 3 PG III



ArmorUltra Military Grade Topcoat Colored 352X- Part A/PAGE 5

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
13463-67-7	Titanium dioxide	No	No	No
Proprietary	Polyester poly-urethane	No	No	No
108-65-6	Propylene glycol methyl ether acetate	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes

All components in this product are listed in the TSCA Inventory List.

V.O.C. (mixed: 3.10LBS/GL. (372 GMS/L)

16. Other Information

Revision Date: 2/23/2023

Additional Information About this Product:

Hazardous Material Information System III (U.S.A)

Health: 2*

Flammability: 3

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Armorpoxy Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

SAFETY DATA SHEET
ArmorUltra Military Grade Topcoat 332/337/352 - Part B



Page 1 – 2/23/2023

1. Product and Company Identification

Product Code: ARM321X-332X-B
Product Name: ArmorUltra Military Grade Topcoat 332/337/352 - Part B
Trade Name: ArmorUltra Military Grade Topcoat 332/337/352 - Part B
Company Name: Armorpoxy Inc.
1260 North Ave
Plainfield, NJ 07062
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
888-755-7361

2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2A
Respiratory Sensitization, Category 1
Flammable Liquids, Category 3
Target Organ Systemic Toxicity (single exposure), Category 3
Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Acute Toxicity: Inhalation, Category 4



GHS Signal Word: **Danger**

GHS Hazard Phrases: H226 - Flammable liquid and vapor.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P260 – Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P285 - In case of inadequate ventilation wear respiratory protection.

GHS Response Phrases: P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501-Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal Phrases:

ArmorUltra Military Grade Topcoat 332/337/352 - Part B/PAGE 2

Potential Health Effects (Acute and Chronic):

Chronic inhalation may cause effects similar to those of acute inhalation.

Inhalation:

Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact:

May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

Eye Contact:

Causes eye irritation. Causes redness and pain.

Ingestion:

May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May

cause

gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
28182-81-2	Poly(hexamethylene diisocyanate)	70.0 – 80.0%
123-86-4	Butyl acetate	10.0 – 20.0%
1330-20-7	Xylene (mixed isomers)	10.0 – 20.0%
100-41-4	Ethylbenzene	0.1 – 4.0%

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact:

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water of water. Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions:

Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid: Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Flammable Properties and Hazards:

Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case

Personal precautions.

Material is Released or Spilled:

Use personal protective equipment.

Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions to be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist.

Precautions to be Taken in Storing:

Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks, and open flame.

ArmorUltra Military Grade Topcoat 332/337/352 - Part B/PAGE 3

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
28182-81-2	Poly(hexamethylene diisocyanate)	N/A	N/A
123-86-4	Butyl acetate	PEL: 150 ppm	TLV: 150 ppm STEL: 200 ppm
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation, etc.)

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Flash Point:	80°F		
Boiling Point:	300°F		
Explosive Limits:	LEL: 1.0	UEL: 7.5	
Weight Per Gallon:	8.8 +/- .25		
Vapor Pressure (mm Hg):	8.4 @ 68°F		
Vapor Density:	Heavier than Air		
Evaporation Rate:	Slower than Ether		
Percent Volatile:	30		

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/>	Stable <input checked="" type="checkbox"/>
Conditions to Avoid - Instability:	Heat, flames and sparks:	
Incompatibility – Materials To Avoid:	Bases, Strong oxidizing agents.	
Hazardous Decomposition Or Byproducts:	Nature of decomposition products unknown.	
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/>	Will not occur <input checked="" type="checkbox"/>

11. Toxicological Information

Toxicological Information:


Other information on acute toxicity. No data available.
Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available.
Teratogenicity: No data available.

Specific target organ toxicity -single exposure (Globally Harmonized System) Specific target organ toxicity – repeated exposure (Globally Harmonized System)
Aspiration hazard. Epidemiology: No information found.
Teratogenicity: Exposure to n-butyl acetate vapors throughout gestation did not cause significant teratogenicity in rabbits, rats, or mice.
Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: Acute toxicity. No data available.
Serious eye damage/eye irritation:
No data available.

Irritation or Corrosion:
Sensitization:

ArmorUltra Military Grade Topcoat 332/337/352 - Part B/PAGE 4

Chronic Toxicological Effects: No data available.
Carcinogenicity/Other Information: Carcinogenicity.
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

 This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene.

12. Ecological Information

General Ecological Information: No data available
Persistence and Degradability: No data available
Bioaccumulative Potential: No data available
Mobility in Soil: No data available

13. Disposal Consideration

Waste Disposal Method: Dispose of as unused product. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):
DOT Proper Shipping Name: Limited Quantity – 1 gallon or quart containers when shipped in the United States of America
UN1263, Paint Related Material, 3, PG III – 5 gallon and 55 gallon drums shipped in the United States of America



IMDG Shipping Name: UN1263, Paint Related Material, 3, PG III



AIR TRANSPORT (ICAO/IATA):
IATA Shipping Name: UN1263, Paint Related Material, 3, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Polyester poly-urethane	No	No	No
123-86-4	Butyl acetate	No	Yes 5000 LB	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes

All components in this product are listed in the TSCA Inventory List.

V.O.C. mixed: 3.25 LBS/GL (389 GMS/L)

ArmorUltra Military Grade Topcoat 332/337/352 - Part B/PAGE 5

16. Other Information

Revision Date: 2/23/2023

Additional Information about this Product:

Hazardous Material Information System III (U.S.A)

Health: 2*

Flammability: 3

Reactivity: 1

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Armorpoxy Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

