



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **SILCON - ROOFING EPOXY 2-PART PRIMER PART A**
CHEMICAL FAMILY NAME: Epoxy Primer
U.N. NUMBER: Not Regulated
U.N. DANGEROUS GOODS CLASS: Not Regulated
SUPPLIER/MANUFACTURER'S NAME: **Armorpoxy Inc.**
ADDRESS: 1260 North Ave, Plainfield, NJ 07062 USA
EMERGENCY PHONE: **TOLL-FREE - Chemtrec 1-800-424-9300**

BUSINESS PHONE: 888-755-7361
WEB SITE: www.armorpoxy.com
DATE OF CURRENT REVISION: Feb 20, 20223
DATE OF LAST REVISION: Feb 4, 2022

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a viscous liquid, white in color with a faint aromatic odor.
Health Hazards: Exposure to the product may cause skin and eye irritation. May cause an allergic skin reaction.
Flammability Hazards: This product is flammable with a flash point >212°F (>100°C).
Reactivity Hazards: None known.
Environmental Hazards: This product expected to cause significant adverse effects in the environment.
Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS

See Section 14 for Details

GHS Hazard Symbols



Signal Word: **Warning!**

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE IN ACCORDANCE WITH 29 CFR 1200 (OSHA HCS) AND THE EUROPEAN UNION DIRECTIVES:

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 AND the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS:

EC# 500-033-5 Annex VI Index# 603-074-00-8

Substances not listed either individually or in group entries must be self classified

Component(s) Contributing to Classification(s)

Bisphenol A-epichlorohydrin polymer

GHS Hazard Classification(s):

Skin Irritation Category 2

Eye Irritation Category 2A

Skin Sensitization Category 1

Hazard Statement(s):

H315: Causes skin irritation

H319: Causes serious eye irritation

H317: May cause an allergic skin reaction

Prevention Statement(s):

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

Response Statement(s):

P302+P352: IF ON SKIN: Wash with plenty of water.
 P312: Call a POISON CENTER/doctor if you feel unwell.
 P321: Specific treatment (See Section 4 of this SDS).
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364: Take off contaminated clothing and wash it before reuse.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice/attention.

Storage Statement(s):

None applicable

Disposal Statement(s):

None applicable

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

This product does not meet the criteria for PBT or vPvB in accordance with Annex XIII

ACUTE: This material may cause irritation to skin, respiratory system and eyes. Ingestion of this product may cause gastrointestinal irritation.

CHRONIC: Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

TARGET ORGANS: ACUTE: Eye, Skin, Respiratory System CHRONIC: None known

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS #	EINECS #	ICSC #	WT %	HAZARD CLASSIFICATION
Bisphenol A-epichlorohydrin polymer	25068-38-6	500-033-5	Not Listed	10-45%	SKIN IRRIT CAT 2, EYE IRRIT. CAT 2A, SKIN SENS CAT 1
Titanium Dioxide	13463-67-7	236-675-5	0338	5 – 10%	CARC. CAT 2 (** THESE MATERIALS ARE BOUND IN LIQUID/PAINT AND ARE NOT AIRBORNE OR IN DUST FORM.)
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

SECTION 4 - FIRST-AID MEASURES

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, respiratory or eye problems may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): Not Established Upper (UEL): Not Established

FIRE EXTINGUISHING MATERIALS: Carbon dioxide, foam, dry chemical, halon, water spray.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

UNUSUAL FIRE AND EXPLOSION HAZARDS:

This material is flammable above flash point shown above.


Explosion Sensitivity to Mechanical Impact:
Explosion Sensitivity to Static Discharge:

Not Sensitive.
 Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)			2
FLAMMABILITY HAZARD (RED)			1
PHYSICAL HAZARD (YELLOW)			0
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	See Sect 8		See Sect 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Keep container tightly closed and in a dry and cool place.

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Bisphenol A-epichlorohydrin polymer	25068-38-6	Not Listed	Not Listed
Titanium Dioxide	13463-67-7	10 mg/m ³	15 mg/m ³

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
APPEARANCE & ODOR:	White viscous liquid with a faint aromatic odor
ODOR THRESHOLD (PPM):	Not Available
FLASH POINT:	Not Available
AUTOIGNITION TEMPERATURE:	Not Available
VAPOR PRESSURE (mmHg):	Not Available
REALTIVE DENSITY:	1.405
DENSITY:	Not Available
EVAPORATION RATE (nBuAc = 1):	Not Available
BOILING POINT (C°):	Not Available
FREEZING POINT (C°):	Not Available
pH:	Not Available
VISCOSITY, Dynamic	6500 - 12000 cPs
SOLUBILITY IN WATER (%)	Not Available
EXPLOSIVE PROPERTIES:	Not Available
OXIDISING PROPERTIES:	Not Available

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: May include, and are not limited to: oxides of carbon.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Heat. Incompatible materials.

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA: Toxicity data is not available for this product:

Bisphenol A-epichlorohydrin polymer (25068-38-6)

LD50 oral rat 13600 mg/kg

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Irritation Category 2A
Respiratory or skin sensitization	Skin Sensitization Category 1
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

SUSPECTED CANCER AGENT: Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin respiratory system and eyes.

SENSITIZATION OF PRODUCT: This product is considered a skin sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No reported information concerning the effects of this product and its components on the human reproductive system.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: None known

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: None known

ASPIRATION HAZARD: None

SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

TOXICITY: No specific data available on this product.

PERSISTENCE AND DEGRADABILITY: No specific data available on this product.

BIOACCUMULATIVE POTENTIAL: No specific data available on this product.

MOBILITY IN SOIL: No specific data available on this product.

RESULTS OF PBT AND vPvB ASSESMENT: No specific data available on this product.

OTHER ADVERSE EFFECTS: No specific data available on this product.

WATER ENDANGERMENT CLASS: Not believed to be water endangering in accordance with EU Guideline 91/155-EWG. At present there are no ecotoxicological assessments for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None listed

EU WASTE CODE: Not Listed

SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT CLASSIFIED AS DANGEROUS GOODS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated Material

HAZARD CLASS NUMBER and DESCRIPTION: None

UN IDENTIFICATION NUMBER: None

PACKING GROUP: None

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2016): None

MARINE POLLUTANT: This products ingredients that are not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization:

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

Harmonized Tariff Code Unknown



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART A

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

SARA 313 REPORTING: Ethylene oxide (75-21-8) 0.1%, 1,4-Dioxane (123-91-1) 0.1%, Acetaldehyde (75-07-0) 0.1%

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: No Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Ingredients contained within this product are on the California Proposition 65 lists.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Classified per WHMIS 2015.

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION:

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: All components of this product are listed or exempt from listing on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPAN INDUSTRIAL SAFETY AND HEALTH LAW: This product has been classified per the Japan Industrial Safety and Health Law. See Section 2 for the GHS Classification.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:	Listed
Australian Inventory of Chemical Substances (AICS):	Listed
Korean Existing Chemicals List (ECL):	Listed
Japanese Existing National Inventory of Chemical Substances (ENCS):	Listed
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Listed
Swiss Giftlist List of Toxic Substances:	Not Listed
U.S. TSCA:	Listed

SECTION 16 - OTHER INFORMATION

PREPARED BY: Armorpoxy Regulatory Department

Disclaimer: The information and recommendations in this document are accurate to the best of our knowledge. User must conduct their own tests to determine the suitability of these products for their particular purposes. Because of numerous factors affecting results, Armorpoxy Inc. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, other than the material conforms to our applicable current specifications. Armorpoxy Inc. assumes no legal responsibility for use or reliance on the information contained in this Material Safety Data Sheet.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **SILCON - ROOFING EPOXY 2-PART PRIMER PART B**
CHEMICAL FAMILY NAME: Epoxy Primer Hardener
U.N. NUMBER: See Section 14
U.N. DANGEROUS GOODS CLASS: See Section 14
SUPPLIER/MANUFACTURER'S NAME: **Armorpoxy Inc.**
ADDRESS: 1260 North Ave, Plainfield, NJ 07062 USA
EMERGENCY PHONE: **TOLL-FREE - Chemtrec 1-800-424-9300**

BUSINESS PHONE: 888-755-7361
WEB SITE: www.armorpoxy.com
DATE OF CURRENT REVISION: Feb 20, 2023
DATE OF LAST REVISION: Feb 4, 2022

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a dark gray viscous liquid with a strong aromatic odor.

Health Hazards: Exposure to the product may cause skin and eye irritation. May cause an allergic skin reaction.

Flammability Hazards: This product is flammable with a flash point >140°F (>60°C).

Reactivity Hazards: None known.

Environmental Hazards: This product expected to cause significant adverse effects in the environment.

Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS

See Section 14 for Details

GHS Hazard Symbols



Signal Word: **Warning!**

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE IN ACCORDANCE WITH 29 CFR 1200 (OSHA HCS) AND THE EUROPEAN UNION DIRECTIVES:

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 AND the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS:

EC# 265-199-0 Annex VI Index# 649-356-00-4

EC# 202-436-9 Annex VI Index# 601-043-00-3

Substances not listed either individually or in group entries must be self classified

Component(s) Contributing to Classification(s)

Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines, Solvent naphtha, petroleum, light aromatic, Benzene, 1,2,4-trimethyl-

GHS Hazard Classification(s):

Flammable Liquid Category 4

Skin Irritation Category 2

Eye Irritation Category 2A

Skin Sensitization Category 1

Hazard Statement(s):

H227: Combustible liquid

H315: Causes skin irritation

H319: Causes serious eye irritation

H317: May cause an allergic skin reaction



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

Prevention Statement(s):

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264: Wash hands thoroughly after handling.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response Statement(s):

- P370+P378: In case of fire: Use media defined in Section 5 to extinguish.
- P302+P352: IF ON SKIN: Wash with plenty of water.
- P312: Call a POISON CENTER/doctor if you feel unwell.
- P321: Specific treatment (See Section 4 of this SDS).
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364: Take off contaminated clothing and wash it before reuse.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.

Storage Statement(s):

- P403: Store in a well-ventilated place.

Disposal Statement(s):

- P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Known Hazards:

- None known
- This product does not meet the criteria for PBT or vPvB in accordance with Annex XIII

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE: This material may cause irritation to skin, respiratory system and eyes. Ingestion of this product may cause gastrointestinal irritation.

CHRONIC: Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

TARGET ORGANS: ACUTE: Eye, Skin, Respiratory System CHRONIC: None known

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS #	EINECS #	ICSC #	WT %	GHS HAZARD CLASSIFICATION(S):
Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines	68410-23-1	614-452-7	Not Listed	5-20%	Skin Irritant Cat 2, Eye Irritant Cat 2, Skin Sensitizer Cat 1
Solvent naphtha, petroleum, light aromatic	64742-95-6	265-199-0	Not Listed	5-8%	Flammable Liquid Cat 3, Skin Irritant cat 2, Eye Irritant Cat 2, Aspiration Tox Cat 1
Benzene, 1,2,4-trimethyl-	95-63-6	202-436-9	1433	1-2%	Flammable Liquid Cat 3, Acute Toxicity Cat 4 (inhal), Skin Irritant Cat 2, Eye Irritant Cat 2, STOT SE Cat 3
Carbon Black	133-86-4	215-609-9	Not Listed	0.1-1%	Carcinogenic Cat 2 (** These materials are bound in liquid/paint and are not airborne or in dust form.)
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

SECTION 4 - FIRST-AID MEASURES

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, respiratory or eye problems may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): Not Established Upper (UEL): Not Established


FIRE EXTINGUISHING MATERIALS: Carbon dioxide, foam, dry chemical, halon, water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material is flammable above flash point shown above.

HAZARDS:
Explosion Sensitivity to Mechanical Impact: Not Sensitive.
Explosion Sensitivity to Static Discharge: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM				
HEALTH HAZARD (BLUE)				2
FLAMMABILITY HAZARD (RED)				2
PHYSICAL HAZARD (YELLOW)				0
PROTECTIVE EQUIPMENT				
EYES	RESPIRATORY	HANDS	BODY	
	See Sect 8		See Sect 8	
For Routine Industrial Use and Handling Applications				

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing vapour or mist. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

STORAGE AND HANDLING PRACTICES: Keep container tightly closed and in a dry and cool place.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines	68410-23-1	Not Listed	Not Listed
Solvent naphtha, petroleum, light aromatic	64742-95-6	Not Listed	Not Listed
Benzene, 1,2,4-trimethyl-	95-63-6	Not Listed	Not Listed
Carbon Black	133-86-4	3 mg/m ³	3.5 mg/m ³

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
APPEARANCE & ODOR:	Dark gray viscous liquid with a strong aromatic odor
ODOR THRESHOLD (PPM):	Not Available
FLASH POINT:	> 60 °C (> 140 °F)
AUTOIGNITION TEMPERATURE:	Not Available
VAPOR PRESSURE (mmHg):	Not Available
REALTIVE DENSITY:	1.39
DENSITY:	Not Available
EVAPORATION RATE (nBuAc = 1):	Not Available
BOILING POINT (C°):	Not Available
FREEZING POINT (C°):	Not Available
pH:	Not Available
VISCOSITY, Dynamic	70000 - 150000 cPs
SOLUBILITY IN WATER (%):	Not Available
EXPLOSIVE PROPERTIES:	Not Available
OXIDISING PROPERTIES:	Not Available



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: May include, and are not limited to: oxides of carbon.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Heat. Incompatible materials.

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA: Toxicity data is not available for this product:

Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines (68410-23-1)

LD50 oral rat > 2000 mg/kg

LD50 dermal rat > 2000 mg/kg

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat 8400 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 inhalation rat >5.2 mg/L/4h

Benzene, 1,2,4-trimethyl- (95-63-6)

LD50 oral rat 3400 mg/kg

LD50 dermal rabbit > 3160 mg/kg

LC50 inhalation rat 18 g/m³/4h

Carbon black (1333-86-4)

LD50 oral rat >15400 mg/kg

LD50 dermal rat >3000 mg/kg

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Irritation Category 2A
Respiratory or skin sensitization	Skin Sensitization Category 1
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

SUSPECTED CANCER AGENT: Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin respiratory system and eyes.

SENSITIZATION OF PRODUCT: This product is considered a skin sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No reported information concerning the effects of this product and its components on the human reproductive system.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: None known

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: None known

ASPIRATION HAZARD: None

SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

TOXICITY: No specific data available on this product.

PERSISTENCE AND DEGRADABILITY: No specific data available on this product.

BIOACCUMULATIVE POTENTIAL: No specific data available on this product.

MOBILITY IN SOIL: No specific data available on this product.

RESULTS OF PBT AND vPvB ASSESMENT: No specific data available on this product.

OTHER ADVERSE EFFECTS: No specific data available on this product.

WATER ENDANGERMENT CLASS: Not believed to be water endangering in accordance with EU Guideline 91/155-EWG. At present there are no ecotoxicological assessments for this product.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None listed

EU WASTE CODE: Not Listed

SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS CLASSIFIED AS DANGEROUS GOODS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Combustible liquid, n.o.s. (Petroleum)

HAZARD CLASS NUMBER and DESCRIPTION: Class 3, Flammable Liquid

UN IDENTIFICATION NUMBER: NA1993

PACKING GROUP: III

DOT LABEL(S) REQUIRED: Combustible

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2016): 128

MARINE POLLUTANT: This products ingredients that are not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization:

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

Harmonized Tariff Code Unknown

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

SARA 313 REPORTING: Benzene, 1,2,4-trimethyl- (95-63-6) 1%

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: Yes Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Ingredients contained within this product are on the California Proposition 65 lists.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Classified per WHMIS 2015.

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION:

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.



SAFETY DATA SHEET

SILCON - ROOFING EPOXY 2-PART PRIMER PART B

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: All components of this product are listed or exempt from listing on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPAN INDUSTRIAL SAFETY AND HEALTH LAW: This product has been classified per the Japan Industrial Safety and Health Law. See Section 2 for the GHS Classification.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:	Listed
Australian Inventory of Chemical Substances (AICS):	Listed
Korean Existing Chemicals List (ECL):	Listed
Japanese Existing National Inventory of Chemical Substances (ENCS):	Listed
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Listed
Swiss Giftlist List of Toxic Substances:	Not Listed
U.S. TSCA:	Listed

SECTION 16 - OTHER INFORMATION

PREPARED BY: Armorpoxy Regulatory Department

Disclaimer: The information and recommendations in this document are accurate to the best of our knowledge. User must conduct their own tests to determine the suitability of these products for their particular purposes. Because of numerous factors affecting results, Armorpoxy Inc. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, other than the material conforms to our applicable current specifications. Armorpoxy Inc. assumes no legal responsibility for use or reliance on the information contained in this Safety Data Sheet.

End of SDS Sheet