

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A**
- **Article number: ARMUFSKX**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 Armor UltraFast LT is a Polyaspartic coating that is used to seal concrete floors.
- **Application of the substance / the preparation** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
 Armorpoxy Inc
 1260 North Ave
 Plainfield NJ 07062
 Phone: 888-755-7361
 Toll-Free:
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number: Chemtrec: 1-800-424-9300**



2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36/38: Irritating to eyes and skin.

R10: Flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

(Contd. on page 2)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 1)

· **2.2 Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Warning· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Hazard description:**· **WHMIS-symbols:**

B3 - Combustible liquid

D2B - Toxic material causing other toxic effects



(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 2)

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



* - Indicates a long term health hazard from repeated or prolonged exposures.

· HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

	Mixed Aspartic Esters ☒ Xi R38 ⚠ Skin Irrit. 2, H315	> 50%
CAS: 98-56-6 EINECS: 202-681-1	4-chloro-alpha,alpha,alpha-trifluorotoluene ☒ Xi R36/38 R10 ⚠ Flam. Liq. 3, H226 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 623-91-6 EINECS: 210-819-7	diethyl fumarate ☒ Xn R22 ⚠ Acute Tox. 4, H302	< 10%
CAS: 6864-37-5 EINECS: 229-962-1 Index number: 612-110-00-1	2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine) ☠ T R23/24; ☒ C R35; ☒ Xn R22; ☒ N R51/53 ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331 ⚠ Skin Corr. 1A, H314 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302	< 1,0%

· Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 4)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 3)

4 First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
 Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.
- **After eye contact:**
 Protect unharmed eye.
 Remove contact lenses if worn.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
 Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
 Allergic reactions
 Dizziness
 Gastric or intestinal disorders
- **Hazards** Condition may deteriorate with alcohol consumption.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 If swallowed, gastric irrigation with added, activated carbon.
 Monitor circulation.
 If necessary oxygen respiration treatment.
 Medical supervision for at least 48 hours.
 Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** None.
- **5.2 Special hazards arising from the substance or mixture**
 In case of fire, the following can be released:
 Hydrogen fluoride (HF)
 Nitrogen oxides (NO_x)
 Carbon monoxide (CO)
 Hydrogen chloride (HCl)
 Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:**
 Wear self-contained respiratory protective device.
 Wear fully protective suit.

(Contd. on page 5)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 4)

- **Additional information** Cool endangered receptacles with water haze or fog.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Ensure adequate ventilation
 Keep away from ignition sources.
 Protect from heat.
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Send for recovery or disposal in suitable receptacles.
 Clean the affected area carefully; suitable cleaners are:
 Warm water and cleansing agent
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 Keep away from heat and direct sunlight.
 Avoid splashes or spray in enclosed areas.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Emergency cooling must be available in case of nearby fire.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store in a cool location.
 Store only in the original receptacle.
- **Information about storage in one common storage facility:**
 Do not store together with acids.
 Store away from oxidizing agents.
 Store away from foodstuffs.
 Store away from reducing agents.
- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed receptacles.
 Store receptacle in a well ventilated area.

(Contd. on page 6)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 5)

- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.
Use suitable respiratory protective device when aerosol or mist is formed.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
Fluorocarbon rubber (Viton)
Chloroprene rubber, CR
- **Not suitable are gloves made of the following materials:** PVA gloves

(Contd. on page 7)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 6)

- **Eye protection:**
Contact lenses should not be worn.



Safety glasses

Goggles recommended during refilling

- **Body protection:** Impervious protective clothing
- **Limitation and supervision of exposure into the environment** No special requirements.
- **Risk management measures**
See Section 7 for additional information.
No special requirements.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Amber coloured
Odour:	Petroleum-like
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point: App. 54 °C (129 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure: Not determined.

· Density at 20°C: 1,09 g/cm³ (9.11 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

(Contd. on page 8)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 7)

· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	8,3 g/l (EPA Method <u>24</u>)
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Contact with strong acids releases hydrogen fluoride.
Reacts with catalysts, oxidizing agents and strong alkali.
Strong exothermic reaction with acids.
Contact with acids releases toxic gases.
Contact with acids releases irritant gases.
Flammable.
Reacts with strong alkali.
Reacts with peroxides and other radical forming substances.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Halogenated hydrocarbons
Poisonous gases/vapours
Fluorinated hydrocarbons
Hydrogen fluoride
Corrosive gases/vapours
Ammonia
Nitrogen oxides (NO_x)
Carbon monoxide and carbon dioxide

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 8)

- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitizing effect by skin contact is possible by prolonged exposure.
Sensitizing effect through inhalation is possible by prolonged exposure.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Danger through skin adsorption.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** The product is partly biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential** May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
At present there are no ecotoxicological assessments.
This statement was deduced from products with a similar structure or composition.
The declarations are valid for the component with the highest toxicological risk.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

(Contd. on page 10)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 9)

- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Solvent naphtha

14 Transport information

- **14.1 UN-Number**
- **DOT** UN1993
- **ADR, IMDG, IATA** UN1993

- **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT** FLAMMABLE LIQUID, N.O.S.
(CHLOROBENZOTRIFLUORIDES)
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S.
(CHLOROBENZOTRIFLUORIDES)
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S.
(CHLOROBENZOTRIFLUORIDES)

- **14.3 Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids.
- **Label** 3

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.

(Contd. on page 11)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 10)

· Label	3
· 14.4 Packing group · DOT, ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids. 30 F-E, S-E
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADR · Tunnel restriction code	D/E
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (CHLOROBENZOTRIFLUORIDES), 3, III

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet
 according to 1907/2006/EC (REACH),
 1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 11)

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R22 Harmful if swallowed.
- R23/24 Toxic by inhalation and in contact with skin.
- R35 Causes severe burns.
- R36/38 Irritating to eyes and skin.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 13)

Safety Data Sheet
according to 1907/2006/EC (REACH),
1272/2008/EC (CLP), and GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part A

(Contd. of page 12)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier: ARMUFSKX Part B**
- **Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B**
- **Article number:**
243802, 243805, 244802, 244805, 244002, 244005, 243002, 243005
Satin or Gloss Products
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Armor UltraFast LT is a Polyaspartic coating that is used to seal concrete floors.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Armorpoxy Inc
1260 North Ave
Plainfield NJ 07062
Phone: 888-755-7361
Toll-Free:
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number: Chemtrec: 1-800-424-9300**



2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H332 Harmful if inhaled.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 1)



Xi; Irritant

R36/38: Irritating to eyes and skin.



F; Highly flammable

R10: Flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Warning

- **Hazard-determining components of labelling:**

Hexane, 1,6-diisocyanato-, homopolymer
hexamethylene-di-isocyanate
4-chloro- α,α,α -trifluorotoluene

- **Hazard statements**

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves / eye protection.
P261 Avoid breathing mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Contains isocyanates. May produce an allergic reaction.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 2)

Can become flammable in use.

- **Hazard description:**

- **WHMIS-symbols:**

B3 - Combustible liquid

D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

- **HMIS Long Term Health Hazard Substances**

None of the ingredients is listed.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 98-56-6 EINECS: 202-681-1	4-chloro- α,α,α -trifluorotoluene ☒ Xi R43; ☒ N R51/53 R10 ☒ Flam. Liq. 3, H226 ☒ Aquatic Chronic 2, H411 ☒ Skin Sens. 1, H317	> 50%
CAS: 28182-81-2 NLP: 500-060-2	Hexane, 1,6-diisocyanato-, homopolymer ☒ Xn R20; ☒ Xi R37; ☒ Xi R43 ☒ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023




Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 3)

CAS: 822-06-0
EINECS: 212-485-8


Index number: 615-011-00-1

hexamethylene-di-isocyanate

 T R23;  Xn R42/43;  Xi R36/37/38

 Acute Tox. 3, H331

 Resp. Sens. 1, H334

 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;
STOT SE 3, H335

< 0,5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• 4.1 Description of first aid measures

• General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Provide oxygen treatment if affected person has difficulty breathing.

• After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not pull solidified product off the skin.

Immediately remove any clothing soiled by the product.

If skin irritation continues, consult a doctor.

• After eye contact:

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

• 4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Coughing

Breathing difficulty

Nausea

Cyanosis

Unconsciousness

• Hazards

Danger of convulsion.

Condition may deteriorate with alcohol consumption.

• 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation, possible shock treatment.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

If blue colouring appears (lips, ear-lobes, finger-nails), give oxygen treatment as quickly as possible.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

Treat skin and mucous membrane with antihistamine and corticoid preparations.

(Contd. of page 4)

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Hydrogen cyanide (HCN)
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
Danger of receptacles bursting because of high vapour pressure when heated.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Take note of emission threshold.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 5)

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store only in the original receptacle.
 - Provide ventilation for receptacles.
 - Store in a cool location.
- **Information about storage in one common storage facility:**
 - Store away from oxidizing agents.
 - Do not store together with acids.
 - Store away from foodstuffs.
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from humidity and water.
 - Store receptacle in a well ventilated area.
 - Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

822-06-0 hexamethylene-di-isocyanate

REL (USA)	Short-term value: C 0,14* mg/m ³ , C 0,02* ppm Long-term value: 0,035 mg/m ³ , 0,005 ppm *10-min
TLV (USA)	0,034 mg/m ³ , 0,005 ppm
EL (Canada)	Short-term value: C 0,01 ppm Long-term value: 0,005 ppm S
EV (Canada)	0,005 ppm

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Do not inhale gases / fumes / aerosols.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 6)

- **Respiratory protection:**

Use suitable respiratory protective device when aerosol or mist is formed.
Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Contact lenses should not be worn.



Safety glasses

Goggles recommended during refilling

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Clear

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: Undetermined.

- **Flash point:** 43 °C (110 °F)

- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 7)

- **Auto/Self-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapour pressure:** Not determined.
- **Density at 20 °C:** 1,25 g/cm³ (10.38 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** <2 g/L (VOCs - EPA Method 24)
- **9.2 Other information** No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions**
Contact with acids releases toxic gases.
Flammable.
Reacts with alcohols, amines, aqueous acids and alkalis.
Corrodes copper and brass.
Reacts with catalysts.
Reacts with water.
Reacts with humid air.
Reacts with oxidizing agents.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 8)

- **10.5 Incompatible materials:** Contact with acids liberates toxic gas.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides
Hydrogen cyanide (prussic acid)
Poisonous gases/vapours
Irritant gases/vapours

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through skin contact.
Sensitizing effect through inhalation is possible by prolonged exposure.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Danger through skin adsorption.

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential**
Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
This statement was deduced from the properties of the single components.
The product contains materials that are harmful to the environment.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

· **12.6 Other adverse effects** No further relevant information available.

(Contd. of page 9)

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Hand over to hazardous waste disposers.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· Recommended cleansing agents: Solvent naphtha

14 Transport information

· 14.1 UN-Number

· DOT

Not regulated for non-bulk shipments per 49 CF
UN2234

· ADR, IMDG, IATA

· 14.2 UN proper shipping name

· DOT

Not regulated for non-bulk shipments per 49 CF

· ADR

2234 CHLOROBENZOTRIFLUORIDES

· IMDG, IATA

CHLOROBENZOTRIFLUORIDES

· 14.3 Transport hazard class(es)

· DOT

· Class

Not Regulated

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 10)

- **14.4 Packing group**
 - **DOT** Not Regulated
 - **ADR, IMDG, IATA** III
 - **14.5 Environmental hazards:**
 - **Marine pollutant:** No
 - **14.6 Special precautions for user** Warning: Flammable liquids.
 - **Danger code (Kemler):** 30
 - **EMS Number:** F-E, S-E
 - **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
 - **Transport/Additional information:**
-
- **ADR**
 - **Limited quantities (LQ)** 5L
 - **Transport category** 3
 - **Tunnel restriction code** D/E
 - **UN "Model Regulation":** UN2234, CHLOROBENZOTRIFLUORIDES, 3, III

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

822-06-0 | hexamethylene-di-isocyanate

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 11)

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

822-06-0 | hexamethylene-di-isocyanate

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients is listed.

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R20 Harmful by inhalation.

R23 Toxic by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R42/43 May cause sensitisation by inhalation and skin contact.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Revision: 02.20.2023

Trade name: Armor UltraFast LT - Low Temp Fast Drying Polyaspartic Coating Part B

(Contd. of page 12)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 3: Acute toxicity, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2